
Time: 3 Hrs Marks: 80

## Note:

- 1. Question **No.1** is **compulsory.**
- 2. Attempt **any three** from the remaining questions.
- 3. Assume suitable data if required.
- 4. Figures on the right hand side indicate full marks.
- 1. a) Design Circulator using Magic Tee. (05)
  - b) Explain Amplification Process in TWT. (05)
  - c) Compare Isolator and Gyrator. (05)
  - d) Calculate S parameters for 3dB Attenuator. Assume  $Zo = 50 \Omega$  (05)



- 2. a) Explain the significance of RWH theory and explain two valley models in GUNN diode. (10)
  - b) What is the importance of beam coupling coefficient? Derive the expression for velocity modulation in two cavity klystron. (10)
- a) Derive the expression for various parameters that describe the wave propagation in TE/TM mode in Rectangular Waveguide (10)
  - b) Explain Impedance measurement Technique in microwave. (10)
- 4. a) Design a two lumped element matching network at frequency 500 MHz frequency to match
  - $Z_L = 200$ -j100 ohms with a transmission line of Zo=100 ohms using Smith Chart. (10)
  - b) Draw and explain two-hole directional coupler and derive the S-parameter for the same. (10)
- 5. a) Design two single stub matching network (shunt- short) for a given load of 60-j80 ohms to match with a 50 ohms transmission line using Smith Chart. (10)
  - b) Compare HMICs and MMICs with suitable diagram. (10)
- 6. Write short note on any two (20)
  - a) Magnetron
  - b) Transit time diodes
  - c) HEMT

\*\*\*\*\*