

M.Tech(with Credits)-Regular-Semester 2012-Structural Engineering & Construction Sem II
STC203 - Design of Substructures

P. Pages : 1

Time : Four Hours



GUG/W/16/3971

Max. Marks : 70

- Notes :
1. All questions are compulsory.
 2. Assume suitable data wherever necessary.
 3. I.S.I. Hand Book for structural steel section. I.S. Code 8000/1962 or 1964, I.S. 456 (Revised), I.S. 875 may be consulted.

1. Design a combined footing for column C1 & C2 having sizes 600 x 600 mm & 500 x 500mm respectively. The column C1 carries 800 KN axial load, C2 carries 600 KN axial load and 100 KN bending moment in front plane of column. C/C distance between C1 & C2 is 2.5m SBC of soil is 180 KN/m². Use M25 grade concrete & Fe 500 grade steel. Sketch rein details. **35**

OR

2. Design a inverted T annular raft for four columns forming a rectangle in plan of size 3m x 6m c/c. The each column carries axial load of 1200KN & has a size 700 x 700mm SBC of soil is 120KN/m². F_{ck} = 25 MPa, F_y = 415 MPa. Sketch rein. details **35**

3. Design a pile & pile cap for a column 600 mm in dia. carrying 700 KN axial load & 150 KNm bending moment. The SBC of soil is 100 KN/m² & negative skin friction is 40 KN/m². Diameter of piles is limited to 300 mm. F_{ck} = 25MPa, F_y = 500 MPa Sketch rein. details. **35**

OR

4. Design counterfort retaining wall to retain earth filling up to 5.5 m height. Density of filling soil is 17 KN/m³ and angle of repose is 30°. SBC of soil is 180 KN/m². Angle of repose of foundation soil is 31° F_{ck} = 25MPa, F_y = 500 MPa Sketch rein. details. **35**
