

B.E. Mechanical Engineering Fourth Semester  
**ME405 - Hydraulic Machines**

P. Pages : 3

Time : Three Hours



**GUG/W/18/1583**

Max. Marks : 80

- Notes :
1. All questions are compulsory. Solve Q. 1 or Q. 2, Q. 3 or Q. 4, Q. 5 or Q. 6, Q.7 or Q. 8 and Q. 9 or Q. 10.
  2. All questions carry marks as indicated.
  3. Assume suitable data wherever necessary.
  4. Illustrate your answers wherever necessary with the help of neat sketches.
  5. Use of non programmable calculator and Drawing instruments.

1. a) Derive the expression for work done by a water jet when it strikes normally series of flat plates mounted on a periphery of a wheel. Also derive the condition for maximum efficiency. 7
- b) A jet of water having a velocity of 35 m/sec impinges on series of vanes moving with a velocity of 20 m/sec. The jet makes an angle of  $30^\circ$  to the direction of motion of vanes when entering and leaves at an angle of  $120^\circ$ . 9  
Draw the velocity triangles and find -  
i) the angles of vane tips so that water enters and leaves without shock  
ii) Work done/kg of water striking the vanes and  
iii) Efficiency
- OR**
2. a) Give reasons in brief **any three**. 7
- i) Pelton turbines are preferred for heads above 170 m.
- ii) Water jet is turned through  $160-170^\circ$  inside the Pelton bucket.
- iii) Pelton Bucket's lower portion is cut-off.
- iv) Pelton turbines do not employ draft tubes.
- b) A Pelton wheel is supplied with  $5 \text{ m}^3/\text{sec}$  when working under a head of 256 M. 9  
Assuming overall efficiency of 85% and coefficient of velocity for nozzle and speed ratio being 0.98 and 0.46 respectively calculate :  
i) Shaft Power  
ii) Diameter of the wheel and jet diameter  
iii) No. of Buckets and its dimensions.  
iv) Specific speed  
Assume the turbine runs at 500 rpm.
3. a) What is a draft tube ? Discuss its types and function. 7

- b) The following data is available for a Francis turbine : 9  
 Net head = 70 m  
 Speed = 600 rpm  
 Shaft power = 370 kW  
 Overall efficiency = 80%  
 Hydraulic efficiency = 95%  
 Flow ratio = 0.25  
 Breadth ratio = 0.1  
 Outer diameter of runner = 2 x Inner diameter of runner  
 thickness of vanes occupies 10% of the circumferential area of the runner and if velocity of flow remains constant and water leaves the turbine radially then determine :  
 i) guide blade angle  
 ii) runner vane angles at inlet & outlet  
 iii) runner diameter at inlet and outlet  
 iv) blade width at inlet & outlet

**OR**

4. a) What is cavitation ? How can we avoid it at design stage or in operation. 7  
 b) A Kaplan turbine runner is to be designed to develop 9000 kW. The net available head is 6m. if the speed ratio is 2.0 and flow ratio is 0.7, over all efficiency 87% and the diameter of boss being 1/3 of the diameter of the runner. Find the diameter of the runner, its speed and specific speed of the turbine. 9
5. a) What is priming of a centrifugal pump ? Why is it necessary. 6  
 b) A centrifugal pump having outer diameter equal to two times the inner diameter and running at 1000 rpm works against a total head of 40 m. 10  
 The velocity of flow through the impeller is constant and equal to 2.5 m/sec. The vanes are set back at an angle of 40° at outlet. If the outer diameter of the impeller is 50 cm and the width at the outlet is 5 cm, determine,  
 i) the vane angle at the inlet  
 ii) work done / sec by impeller on water  
 iii) manometric efficiency  
 Draw the velocity triangles at inlet and exit tips of vane.

**OR**

6. a) Show that for a centrifugal pump pressure rise inside the impeller can be given by the expression 10  

$$\frac{P_2 - P_1}{w} = \frac{1}{2g} \left[ v_{f1}^2 + u_2^2 - v_{f2}^2 \cos^2 \beta_2 \right] \text{ where}$$
 $v_{f1}$  and  $v_{f2}$  are velocities of flow at inlet & outlet tip of vane respectively and  $u_2$  is the peripheral velocity at the outlet tip.  $\beta_2$  is the blade angle at the outlet tip.
- b) Write in short about the following **any two**. 6  
 i) Pumps arranged in series and parallel.  
 ii) N.P.S.H.  
 iii) Self Priming pumps.

7. a) What do you understand by coefficient of discharge of a reciprocating pump. What is its relationship with slip? Can slip be negative? If yes, how? 7
- b) A single acting reciprocating pump has a cylinder of 10 cm diameter and 20 cm stroke. Suction and delivery heads for the pump are 4m and 15 m respectively. Suction pipe has 5 cm diameter and 5 m length while delivery pipe has 4 cm diameter and 20 m length. If separation occurs at 2.4 m of water, find the maximum speed at which pump should be operated without causing separation. 9

**OR**

8. a) Explain the working of air vessels fitted on reciprocating pumps in brief. 7
- b) Write in short **any three**. 9
- i) Gear pumps.
- ii) Vane pumps
- iii) Hand Pumps
- iv) Actual Indicator diagrams.
9. a) Derive the expression for specific speed of a turbine. 7
- b) A turbine model working under a head of 2m runs at 170 rpm and has a diameter of 1m. A prototype turbine develops 22 MW under a head of 250 m with a specific speed of 100. Calculate - 9
- i) the scale ratio
- ii) power developed by the model.

**OR**

10. Write short notes **any four**. 16
- i) Regenerative or peripheral pumps.
- ii) Hydraulic Ram
- iii) Types of similarities.
- iv) Jet pumps
- v) Unit Quantities.

\*\*\*\*\*

[munotes.in](http://munotes.in)